



- 1 - POWER SWITCH - 10A @ 230V, 2-POLE (ESW-130)
- 2 - POWER RELAY - DDPDT, 30A, 240VAC (ERL-030)
- 3 -
- 4 - UNIT COOLER - 0.8A, 220V, 50/60Hz (RCO-052)
- 5 - POWER CORD - 3-WIRE, 16A, 230VAC (ECD-024)
- 6 - CONDENSING UNIT - 230/1/50, 4.3A (RCU-313)
- 7 - CONTROLLER W/ OVERLAY - 85-264VAC, 50/60Hz (ETC-108 & ETC-109)
- 8 - TEMPERATURE SENSOR - RTD, 100 Ohm, 0.00385 Ohm/Ohm/°C (ETC-052)
- 9 - RELAY - NO, 3-32VDC INPUT, 24-240VAC, 25A (ERL-060)
- 10 - HEATER - 250W @ 230VAC, 1.1A (EHE-046)
- 11 -
- 12 - SOLENOID VALVE - 3/8" LINE, 240VAC/1/50 (RVS-027, -028, -031)
- 13 - SOLENOID VALVE - 1/4" LINE, 240VAC/1/50 (RVS-027, -028, -030)
- 14 -
- 15 - TERMINAL BLOCK - WAGO, SERIES 2004, AWG 20-10, 30A, 600V

- 16 -
- 17 -
- 18 -
- 19 - POWER SUPPLY - 95-265VAC INPUT, 12VDC, (EPS-033)
- 20 -
- 21 -
- 22 -
- 23 -
- 24 -
- 25 -
- 26 -
- 27 -
- 29 -
- 30 -

- 31 - CABLE - USB, FEMALE-MALE, 3ft, BLK (EPC-032)
- 32 -
- 33 -
- 34 -
- 35 -
- 36 - TOUCHSCREEN - 10", SIBO, 12VDC/1500mA, 18W (EPC-044)
- 37 - ETHERNET CABLE - 5FT, MALE-MALE, (EPC-057)
- 38 - CIRCUIT BREAKER - 1-POLE, 2A (EBR-147)
- 39 - CIRCUIT BREAKER - 1-POLE, 3A (EBR-163)
- 40 -
- 41 -
- 42 -
- 43 - CIRCUIT BREAKER - 1-POLE, 15A (EBR-146)
- 44 -
- 45 -

REFER TO LIGHTING ELECTRICAL SCHEMATIC:

ELECTRICAL SYSTEM CHARACTERISTICS		
VOLTAGE	230 VAC	PHASE: 1Ø
		FREQUENCY: 50 Hz
AMPERAGE DRAW (MAX)		
MODEL #	CORD #1	RLA / MCA
ARC-36L	7.8A	7.8A/10.0A

PERCIVAL SCIENTIFIC, INC.		
TITLE: ELECTRICAL SCHEMATIC - GENERAL		
MODEL: ARC-36L	DRAWING: 034275-0-1	
BY: SE	DATE: 7/23/2024	